SPECTRUM PAINT®

PRODUCT DATA SHEET

SPEC-PRO® Above™ Interior Latex Ultra Flat Ceiling & Wall Paint (A37100)

Product Description

Spec-Pro® Above™ Interior Latex Ultra Flat Ceiling & Wall Paint is formulated to produce a seamless, ultra-flat finish on interior surfaces. It is a professional-quality flat coating that offers fast drying, low spatter, and excellent touch-up characteristics. The smooth, ultra-flat finish also helps reduce labor costs by hiding surface imperfections.

Where to Use

Formulated for use as a finish coat on residential or commercial interior ceilings and walls constructed of plaster, wallboard, wood, or masonry.

Product Characteristics

Color Bright White

Sheen Ultra Flat

Architectural and Industrial Maintenance Category Flat Coatings

Drying Time

Temperature	To Touch	To Recoat
75°F / 55% R.H.	1-2 hours	4 hours

(Cooler temperatures and higher humidity will lengthen dry time)

Preparation & Priming

Surface Preparation Paint only over clean and dry surfaces. Remove all loose paint, oil, grease, dirt, chalk or other contaminants that would hinder the performance of the coating. Mildew must be killed by scrubbing with a solution of a non-soapy detergent such as T.S.P. (Tri-Sodium Phosphate), household bleach and warm water. Thoroughly rinse affected area and let dry prior to painting. Be sure to wear appropriate splash goggles, cover any exposed skin and have adequate ventilation when handling bleach. Repair all damaged areas and repair any cracks or splits with appropriate caulk or filler. Glossy surfaces should be sanded.

Physical Properties

Mixing Stir thoroughly, making sure no pigment remains on the bottom of the can.

Thinning Do Not Thin

Surface Temperature Minimum 50°F, Maximum 110°F - The surface should be dry, and the relative humidity should be less than 85%.

Recommended Thickness 2.0-4.0 mils dry.

Theoretical Coverage 544 ft²/gallon at 1 mil dry, assuming no application losses. Coverage will vary depending on color, the surface texture and application technique.

Coverage Rates per Coat

	Dry Mills	Wet Mills	Ft²/gal
Suggested	3.0	7.7	181
Minimum	2.0	5.1	272
Maximum	4.0	10.3	136

Application Equipment

Airless Spray	Pressure	1800-2400 psi
	Tip	0.015"-0.019"
Conventional Spray	Air Pressure	40-70 psi
	Fluid Pressure	10-20 psi
Roller	Use a ½" nap or larger soft woven roller.	
Brush	Use high quality synthetic or nylon bristle brushes.	

Application Considerations This coating allows for brush, roller, or spray application. Always apply into rather than away from the wet edge, overlapping each pass 50%. Apply the product in full even coats and maintain a wet edge. Allow the product to dry between coats. Allow the paint to cure at least ten days before cleaning.

Cleanup & Storage

Cleanup	Use soap and warm water to clean up spills. Clean hands and tools immediately after use. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment.	
Storage Temperature	Minimum 35°F	Maximum 110°F

Safety & Important Information

Product contains ethylene glycol. See SDS for important safety information.

Use only with adequate ventilation. Avoid breathing vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Additional Technical Data

Solids by Volume	34% ± 2
Solids by Weight	52% ± 2
Finish	< 5 @ 85°
AIM Category VOC Limit	2.9 lb/gal (350 g/L)
Coating VOC	0.49 lb/gal (58.67 g/L) – Minus Water and Exempt Materials.
Material VOC	0.17 lb/gal (20.93 g/L)
Density	11.56 lb/gal (1483 g/L)
Packaging	5 Gallon pails and 1 Gallon cans.
Safety Information	Refer to the Product Data Sheet or Material Safety Data Sheet for safety information.

Version: 11/2026

Spectrum Paint Company warrants your satisfaction with the application, appearance, and performance properties of this product when applied to a properly prepared surface in accordance with the label directions. **Spectrum Paint makes no other express warranties. If the product fails to conform to this Limited Warranty, Spectrum Paint will, at your option, furnish replacement product or refund the purchase price. This Limited Warranty excludes (1) labor or costs of labor for the application or removal of any product and (2) all other direct, indirect, incidental, special, or consequential damages.** This Limited Warranty gives you specific legal rights; you may have other rights which vary by state. To make a claim under this Limited Warranty, supply dated proof of purchase to the store of purchase or to Spectrum Paint Company, 15247 E. Skelly Dr., Tulsa, OK 74116.