




# ADMIRAL

PRECAT LACQUER

**SPECTRUM  
PAINT®**



Admiral Pre-Catalyzed Lacquers Professional Wood Coatings are designed to offer a fast drying, durable, easy to apply, premium finish. A combination sanding sealer/top coat that dries to a smooth finish. Available sheens include flat, dull-rubbed, satin, semi-gloss, and gloss.

For professional use only.  
Interior Wood substrates only.





## Superior Performance

Admiral Professional Pre-Catalyzed Lacquers are premium, fast-drying wood coatings designed for professional cabinet and furniture makers. They deliver exceptional durability, high-build anti-sag performance, and excellent sandability while meeting stringent industry standards.



## Premium Versatility

Spectrum Paint Admiral Pre-Catalyzed Lacquer is a premium, professional-grade wood finish valued for its incredible versatility. It is Easy to use while maintaining excellent durability and outstanding flexibility. When finishing application require, this system also features primers and sealers.



**Clears**



**Whites**

**Primer**





## FEATURES

- Ready to Spray Viscosity
- Resists Moisture
- Self Sealing
- Meets or exceeds KCMA standards
- Primers and sealers available
- Easy to Apply
- Super-Low HAPs
- Easy Sanding

## FIELD OF APPLICATION

Wood surfaces, kitchen cabinets, store and restaurant fixtures, furniture, and fine architectural woodwork



| PHYSICAL PROPERTIES                            | CLEAR                                                                                                                          | WHITE                                                                             | PRIMER          | SEALER            | SEALER QUICK DRY  |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------|-------------------|-------------------|
| <b>Weight</b>                                  | 7.6 to 8 lbs./gal                                                                                                              | 8.3 - 8.6 lbs./gal                                                                | 8.7 lbs./gal    | 7.6 to 8 lbs./gal | 7.54 lbs./gal     |
| <b>Viscosity at 77° F</b>                      | 26-30" #2 Zahn EZ                                                                                                              | 44-50 KU                                                                          | 62-68 KU        | 23-28" #2 Zahn EZ | 20-25" #2 Zahn EZ |
| <b>Solids Weight</b>                           | 26 to 28%                                                                                                                      | 33 to 35%                                                                         | 34.7%           | 24.3%             | 26.3%             |
| <b>Solids Volume</b>                           | 20 to 22%                                                                                                                      | 20 to 22%                                                                         | 18.1%           | 17.7%             | 19.6%             |
| <b>Resin Type</b>                              | Pre-Catalyzed Lacquer                                                                                                          |                                                                                   |                 |                   |                   |
| <b>Theoretical Coverage</b>                    | 321 to 353 sq. ft./gal                                                                                                         | 321 to 353 sq. ft./gal                                                            | 290 sq. ft./gal | 284 sq. ft./gal   | 314 sq. ft./gal   |
| <b>Flash Point</b>                             | >200° F                                                                                                                        |                                                                                   |                 |                   |                   |
| <b>SKUs</b><br>+<br><b>Sheen (gloss at 60)</b> | 17110 - Flat (7-10°)<br>17210 - Dull (15-20°)<br>17310 - Satin (35-40°)<br>17510 - Semi-Gloss (57-63°)<br>17910 - Gloss (85+°) | 17200 - Dull Rubbed<br>17400-1 - Satin<br>17500-1 - Semi-Gloss<br>17900-1 - Gloss | 17000 - Dull    | 17010             | 16010             |

