



Paint & Primer In One Exterior Satin Finish

DESCRIPTION

A durable 100% acrylic latex satin house paint with a Lifetime warranty when applied according to all label directions on a properly prepared surface

FORMULA ANALYSIS

Resin Type – 100% Acrylic
Sheen/Type Finish: 10-20 @60° / Satin
Weight per Gallon = 10.36 lbs. /gal % \pm .2
Percent Solids by Weight = 50.55 % \pm 2%
Percent Solids by Volume = 40.70 % \pm 2%
Viscosity Range = 95-105 KU
V.O.C. = Less than 50 gm/L 0.042lbs/gal
MPI# 15

RECOMMENDED USE

Exterior new, weathered or previously painted surfaces such as masonry, stucco, concrete block, brick and concrete. May also be used on properly prepared wood, factory primed siding and cement board.

THINNING: Thin sparingly with water if necessary for spray application use .013 - .017 spray tip.

DRY TIME: Dries to the touch in up to 2 hours, recoat in 4 hours. Dry times may vary depending on humidity, temperature, film build and air movement. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant.

COVERAGE: 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal. Do not pour down a drain or storm sewer.

STORAGE: Protect unused product from freezing.

APPLICATION METHODS:

This paint can be used over latex or oil based paint. Intermix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 35°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating.



PRODUCT FEATURES

- High Hiding Formula
- Low temp application 35°
- Exceptional Durability
- Superior Fade Resistance
- Stain & Mildew Resistant
- Superior Chalking Resistance
- Excellent application with brush, roller or spray
- Adheres to difficult substrates

Color and Bases Available

White	D Deep Base
P Pastel Base	N Neutral Base
T Tint Base	



Paint & Primer In One Exterior Semi-Gloss Finish

DESCRIPTION

A durable 100% acrylic latex semi-gloss house paint with a Lifetime warranty when applied according to all label directions on a properly prepared surface

FORMULA ANALYSIS

Resin Type – 100% Acrylic
Sheen/Type Finish: 45-55 @60° /
Semi-Gloss
Weight per Gallon = 10.10 lbs. /gal % ± .2
Percent Solids by Weight = 45.40 % ± 2%
Percent Solids by Volume = 36.00% ± 2%
Viscosity Range = 95-105 KU
V.O.C. = Less than 50 gm/L 0.04 lbs./gal
MPI# 11

RECOMMENDED USE:

Exterior new, weathered or previously painted surfaces such as masonry, stucco, concrete block, brick and concrete. May also be used on properly prepared wood, factory primed siding and cement board.

THINNING: Thin sparingly with water if necessary for spray application use .013 - .017 spray tip.

DRY TIME: Dries to the touch in up to 2 hours, recoat in 4 hours. Dry times may vary depending on humidity, temperature, film build and air movement. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant.

COVERAGE: 250-400. sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal. Do not pour down a drain or storm sewer.

STORAGE: Protect unused product from freezing.

APPLICATION METHODS:

This paint can be used over latex or oil based paint. Intermix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 35°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating



PRODUCT FEATURES

- High Hiding Formula
- Low temp application 35°
- Exceptional Durability
- Superior Fade Resistance
- Stain & Mildew Resistant
- Superior Chalking Resistance
- Excellent application with brush, roller or spray
- Adheres to difficult substrates

Color and Bases Available

White	D Deep Base
P Pastel Base	N Neutral Base
T Tint Base	