



Catalyst Ratios

	Product Number	Description	Catalyst	Catalyzation Rate by Volume	Catalyzation Rate for 1 Quart (32 oz/ 946.25 ml)	Catalyzation Rate for 1 Gallon (128 oz/ 3,785 ml)	Catalyzation Rate for 5 Gallons (640 oz/ 18,927 ml)	Pot Life
Pigmented Products	AUW1260	Ultraguard Conversion Varnish Primer	CXC4000	1.5%	0.5 oz	1.9 oz	9.6 oz	8-12 Hours
	AUW710X	Ultraguard Conversion Varnish White Topcoat	CXC4000	4%	1.3 oz	5.1 oz	25.6 oz	8-12 Hours
Neutral Products	AUF7000	Ultraguard Conversion Varnish Neutral Primer	CXC4000	1.5%	0.5 oz	1.9 oz	9.6 oz	8-12 Hours
	AUF720X	Ultraguard Conversion Varnish Neutral Topcoat	CXC4000	5%	1.6 oz	6.4 oz	32. oz	8-12 Hours
Clear Products	AUS5800	Ultraguard Conversion Varnish Sealer	CXC4000	2%	0.6 oz	2.6 oz	12.8 oz	8-12 Hours
	AUF580X	Ultraguard Conversion Varnish Topcoat	CXC4000	3%	1. oz	3.8 oz	19.2 oz	8-12 Hours

* Please refer to specific product information sheets or can label for mixing instructions and pot life.

** Use only at the recommended ratio. Do not over catalyze.

*** Potlife established at 75°F, 50% RH