



PRODUCT DATA SHEET

SPEC-PRO® 1000 Interior Latex Flat (31101)

Product Description

Spec-Pro® 1000 Interior Latex is a durable, quality interior vinyl acrylic paint designed for new and repaint applications where speed of application is most important in the commercial, new home construction, and multi-family segments. Spec-Pro® 1000 Interior Latex paint has good hide and easy application properties on walls, ceilings and trim surfaces.

Where to Use

Recommended Substrates: Concrete/Masonry, Gypsum Wallboard-Drywall, Concrete Block (CMU), Plaster, Ferrous Metal, and Wood.

Product Characteristics

Color White & Pastel Base

Sheen Flat

Drying Time

Temperature	To Touch	To Recoat
77°F / 50% R.H.	30-60 minutes	2-4 hours

(Cooler temperatures and higher humidity will lengthen drying time)

Surface Preparation

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Plaster, concrete, and masonry surfaces must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to painting. May be used self-priming on new drywall. Prime all bare wood, plaster, masonry, metal, and porous surfaces with an appropriate primer.

CONCRETE/MASONRY: New concrete and masonry should cure for at least 30 days and preferably 90 days prior to priming and painting. The pH of the substrate must be less than 10 before priming. Use of an alkali resistant primer is recommended.

CONCRETE BLOCK (CMU): Mortar should cure for at least 30 days and preferably 90 days prior to painting. Fill block with an appropriate block filler.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed with a metal primer.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust prior to painting the substrate.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming and painting. The pH of the substrate must be less than 10 before priming. Use of an alkali resistant primer is recommended.

WOOD: Countersink all nails, putty flush with surface. Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be sealed before painting.

Physical Properties

Mixing Stir thoroughly, making sure no pigment remains on the bottom of the can.

Thinning Do not thin.

Surface Temperature Minimum 50°F, Maximum 90°F

Coverage Approximately 400 sq. ft. (37 sq. meters) per U.S. Gallon (3.78L) on smooth, nonporous surfaces.

Wet Film Thickness: 4.0 mils
Dry Film Thickness: 1.2 mils

Wet Microns: 102
Dry Microns: 31

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

Application Equipment **Airless Spray** Pressure 2000 psi
Tip 0.015"-0.021"

Roller Use a 3/8" - 3/4" nap roller cover

Brush Use high quality polyester or nylon bristle brushes.

Application Considerations Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. Allow the paint to full cure at thirty days.

Clean-up & Disposal

Cleanup	Use soap and water
Disposal	Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

Safety & Important Information

See SDS for important safety information.

Use only with adequate ventilation. Avoid breathing vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Additional Technical Data

Product Type	Vinyl Acrylic Latex
Sheen	Flat, 0-2 @ 60° & 85°
Volume Solids	31% ± 2
Weight Solids	52% ± 2
Weight/Gallon	12.0 lbs. (5.4 kg) ± 0.2 lbs. (91 g)
VOC	< 50 g/L (0.4 lbs./gal.)
Safety Information	Refer to the Product Data Sheet or Material Safety Data Sheet for safety information.

Version: 1/2026

Spectrum Paint Company warrants your satisfaction with the application, appearance, and performance properties of this product when applied to a properly prepared surface in accordance with the label directions. Spectrum Paint makes no other express warranties. If the product fails to conform to this Limited Warranty, Spectrum Paint will, at your option, furnish replacement product or refund the purchase price. This Limited Warranty excludes (1) labor or costs of labor for the application or removal of any product and (2) all other direct, indirect, incidental, special, or consequential damages. This Limited Warranty gives you specific legal rights; you may have other rights which vary by state. To make a claim under this Limited Warranty, supply dated proof of purchase to the store of purchase or to Spectrum Paint Company, 15247 E. Skelly Dr., Tulsa, OK 74116.