



# SAFETY DATA SHEET

## Section 1: Identification

**Product Code:** A37100

**Product Name:** Spec-Pro® Above™ Interior Latex Ultra Flat Ceiling Paint

**Product Family:** Architectural Latex

**Recommended Use:** Interior Architectural Paint

**Manufactured For:**

Spectrum Paint Co.  
15427 E Skelly Dr  
Tulsa, OK 74116  
1-866-437-5863

**Customer Service:**

Phone: 918-398-2188  
Fax: 918-398-2189

**Emergency Information:**

CHEMTREC	800-424-9300
Poison Control	800-222-1222

## Section 2: Hazards Identification

### GHS Classifications

Eye Damage/Irritation, Category 2A
Carcinogenicity - Category 1B

### Label Elements

**Hazard Pictograms:**



**Signal Word:** Danger

### Hazard Statements:



# SAFETY DATA SHEET

Causes serious eye irritation.

May cause cancer.

## Precautionary Statements:

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label carefully and follow all instructions

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood

Wash thoroughly after handling.

Use protective gloves, clothing and eye protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: get medical advice.

If eye irritation persists: Get medical attention.

Store locked up.

Dispose of contents to an approved waste disposal plant or paint recycling center.

## Other Hazards:

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

## Unknown acute toxicity:

20% of the mixture consists of ingredients of unknown acute toxicity.

## Section 3: Composition/Information on Ingredients

Name	CAS No.	Approx % by Weight
Calcium Carbonate	1317-65-3	35% - 40%

Titanium Dioxide	13463-67-7	5% - 10%
CAS Number not found	34398-01-1	< 1%
Propylene Glycol	57-55-6	1% - 2%
Trade Secret	Trade Secret	< 1%
Water	7732-18-5	30% - 35%
Trade Secret	Trade Secret	< 1%
Calcined Kaolin	92704-41-1	5%-10%
Trade Secret	Trade Secret	< 1%

Full text of H-phrases: see section 16

## **Section 4: First Aid Measures**

### **Eye Contact**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

### **Inhalation**

Avoid fume exposure of the rescuer. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing has stopped, provide artificial respiration or use mouth-to-mouth resuscitation. If symptoms persist, get medical attention.

### **Skin Contact**

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. If irritation occurs, get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### **Ingestion**

Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on side in the recovery position.



# SAFETY DATA SHEET

## **Section 5: Fire-Fighting Measures**

### **Suitable Extinguishing Media**

Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish.

### **Unsuitable Extinguishing Media**

Do not use straight streams of water.

### **Specific hazards arising from the chemical**

Material can splatter above 100C/212F. Polymer film can burn.

### **Hazardous Combustion Products**

Oxides of carbon, metal oxides.

### **Special Protective Equipment and Precautions for Firefighters**

No action shall be taken involving any personal risk or without suitable training. Firefighters should use standard protective equipment and in enclosed spaces, self-containing breathing apparatus (SCBA).

### **Additional Firefighting Instructions**

Evacuate surrounding areas. Use water spray to keep fire-exposed containers cool. Do not allow run-off from fire fighting to enter drains. Collect contaminated fire extinguishing water and dispose of in accordance with local regulations.

## **Section 6: Accidental Release Measures**

### **Personal Precautions, Protective Equipment, and Emergency Procedures**

Avoid breathing vapor. Remove all sources of ignition and avoid static electricity discharges. Use protective equipment as required (See Section 8). Prevent further leakage or spillage if safe to do so. Avoid runoff into storm sewers and ditches which lead to waterways. Keep unauthorized personnel from the area.



# SAFETY DATA SHEET

## **Personal Precautions, Protective Equipment, and Emergency Procedures**

Avoid breathing vapors. Remove all sources of ignition and avoid static electricity discharges. Use protective equipment as required (See Section 8). Prevent further leakage or spillage if safe to do so. Avoid runoff into storm sewers and ditches which lead to waterways. Keep unauthorized personnel from the area.

## **Methods and Materials for Containment and Cleaning Up**

Dam up and soak up with inert absorbent material (floor-dry, PIG absorbents, sand, or sawdust). Scoop up and transfer to properly labeled containers. Allow used absorbent material to dry and dispose of according to local regulations.

Advise local authorities if spillage cannot be contained.

## **Section 7 Handling and Storage**

### **Precautions for Safe Handling**

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking, and smoking in work area is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

### **Conditions for Safe Storage**

Keep containers cool, dry, and away from sources of ignition. Store in well-ventilated area and prevent unauthorized access.

### **Emptied Containers**

Emptied containers may retain product residue and retain all hazards. Do not cut, weld, drill, grind, or expose empty containers to other sources of ignition. Doing so may cause explosion, injury, or death.



# SAFETY DATA SHEET

## Incompatibilities

Strong oxidizers. Ignition sources.

## Section 8: Exposure Controls/Personal Protection

Name	OSHA PEL (TWA)(mg/m3)	OSHA PEL (TWA)(ppm)
Calcium Carbonate (1317-65-3)		
Titanium Dioxide (13463-67-7)	TWA mg/m3: 15	PEL-STEL mg/m3: N/A
Trade Secret CAS Number not in master		
Propylene Glycol (57-55-6)		
Trade Secret CAS Number not in master		
Water (7732-18-5)		
Trade Secret CAS Number not in master		
Calcined Kaolin (92704-41-1)	5	
Trade Secret CAS Number not in master		

## Respiratory Protection

Keep area well ventilated insuring that TLV or PELs are not exceeded. Use forced air movement such as spray booths or fans. If exposure exceeds TLV, PELs, or if personnel experience inhalation irritation, use a NIOSH approved respirator. If a respirator is needed, current engineering controls are not adequate and should be reevaluated.

## Skin Protection

Skin protection is required for prolonged or repeated contact. Wear chemical resistant gloves and impermeous clothing. Liquid may penetrate shoes and other clothing causing delayed irritation. Remove contaminated clothing as soon as possible and wash hands before eating, smoking or using the restroom.

## Eye Protection

Use safety eyewear designed to protect against splash of liquids and vapors.



# SAFETY DATA SHEET

## Other Equipment

Emergency eye wash capability and the ability to wash with soap and water should be readily available. Use NIOSH approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other information: When using, do not eat, drink or smoke.

## Section 9: Physical and Chemical Properties

Information on basic physical and chemical properties:

Appearance	Opaque Liquid
Odor	No Information Available.
Odor Threshold	No Information Available.
pH	8.5 - 10.0
Melting/Freezing Point	25 - 35 F
Boiling Point (Point/Range)	212F to 477F
Flash Point	N.A.
Evaporation Rate	No Information Available.
Flammability	Flash point at or above 200F
UEL	No Information Available.
LEL	No Information Available.
Vapor Pressure	17 mmHg
Vapor Density	Lighter than air (water)
Relative Density	1.47764
Solubility	No Information Available.
Partition Coefficient: n-octanal/water	No Information Available.
Auto-ignition Temperature	No Information Available.
Decomposition Temperature	No Information Available.
Viscosity	No Information Available.
Regulatory VOC:	46.96638 g/l (.39195 lb/gal)
Actual VOC:	18.84120 g/l (.15723 lb/gal)
% Solids By Weight:	58.34331
% Solid By Volume:	38.27399



# SAFETY DATA SHEET

## **Section 10: Stability and Reactivity**

### **Reactivity**

No dangerous reaction known under conditions of normal use.

### **Chemical Stability**

This product is stable.

### **Hazardous Reactions**

Will not occur.

### **Conditions to Avoid**

Decomposition is dependent on time and temperature. Onset of decomposition is 177C 350F. Avoid high temperatures.

### **Incompatible Materials**

Strong oxidizers.

### **Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition should not occur.

## **Section 11: Toxicological Information**

**Information on toxicological effects:**

**Likely Routes of Exposure:**



# SAFETY DATA SHEET

Inhalation, Ingestion, Skin and Eye Contact.

## Inhalation Symptoms/Effects:

May be irritating to the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death.

## Ingestion Symptoms/Effects:

If swallowed, can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

## Skin Contact Symptoms/Effects:

Prolonged or repeated skin contact may defat the skin resulting in possible irritation and dermatitis.

## Delayed or Chronic Effects:

None known.

## Ingredient Toxicity Information:

CAS No./Test	Test Results
Calcium Carbonate (1317-65-3)	
LC50 - Inhalation Rat	
Titanium Dioxide (13463-67-7)	
LC50 - Inhalation Rat	>6.8 mg/l
LD50 - Oral Rat	>10,000 mg/kg
LD50 - Dermal Rabbit	>10,000 mg/kg
Trade Secret CAS Number not in master	
Propylene Glycol (57-55-6)	
LC50 - Inhalation Rat	317,042 mg/m3



# SAFETY DATA SHEET

Trade Secret CAS Number not in master	
Water (7732-18-5)	
Trade Secret CAS Number not in master	
Calcined Kaolin (92704-41-1)	
Trade Secret CAS Number not in master	

## Ingredients with Potential Carcinogenicity:

Name	IARC Group	NTP (National Toxicity Program)
Titanium Dioxide (13463-67-7)	2B	

## Section 12: Ecological Information

### Ecotoxicity:

Based on available data, the classification criteria are not met.

### Persistence and Degradability:

57-55-6 Propylene Glycol

Readily biodegradable

64742-21-1 Isoparaffinic Petroleum Distillate

Expected to be inherently biodegradable. Volatile constituent will photochemically oxidize.

### Bioaccumulation:

No potential for bioaccumulation.

### Mobility:

Air - Liquid components are volatile and will partition to air.



# SAFETY DATA SHEET

Soil - No information available.

### Other Adverse Effects:

No information available.

## Section 13: Disposal Considerations

### Product Stewardship:

The generation of waste should be avoided or minimized wherever possible. Use the spreading rate recommendation in the Product Data Sheet and job size to estimate needed quantities before acquiring product.

### Waste Disposal:

Dispose in accordance with all applicable federal, state, and local regulations. Recycle if a recycling center is available that accepts latex paints.

### Emptied Containers:

Emptied containers may retain product residue and retain hazards. Do not cut, weld, drill, grind, or use for any other purpose. Return drums to reclamation centers for proper disposal.

## Section 14: Transport Information

### Land US Domestic (DOT)

NOT REGULATED

UN Proper Shipping Name: Paint

Environmental Hazard: No

Hazardous Substance: No



# SAFETY DATA SHEET

## Section 15: Regulatory Information

### State or local regulations:

Titanium Dioxide (13463-67-7)
U.S. California Proposition 65 Carcinogens List: WARNING this product contains chemicals known to the state of California to cause cancer.

### Federal Regulations:

Calcium Carbonate (1317-65-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Titanium Dioxide (13463-67-7)
IARC_Carcinogen
SARA 311/312 Hazardous
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Propylene Glycol (57-55-6)
SARA 311/312 Hazardous
Calcined Kaolin (92704-41-1)
SARA 311/312 Hazardous

(See Section 9 for actual VOC content)

### SARA 311/312 Hazard Categories:

Acute Health, Chronic Health

All ingredients are listed or exempt from listing on the following inventories: TSCA, DLS

### California Proposition 65:

This product contains chemicals known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.



# SAFETY DATA SHEET

## Section 16: Other Information

### Data Sources:

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Code/Abbreviation	Description
H319	Causes serious eye irritation.
H350	May cause cancer.

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Anchor Paint Manufacturing Co., Inc. knowledge or obtained from sources believed by Anchor Paint Manufacturing Co., Inc. to be accurate and Anchor Paint Manufacturing Co., Inc. does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests.

### **Manufactured By:**

Anchor Paint Manufacturing Co., Inc  
6707 East 14th Street  
Tulsa, OK 74112  
1-800-999-4629