



## Spec-Pro® Buildermax® Interior Latex Undercoater (34000)

Spec-Pro® Buildermax® Interior Latex Undercoater: Designed specifically for an undercoat for water based acrylic enamels and alkyds. For interior use on properly prepared bare wood, masonry and unpainted wallboard. The excellent holdout, fast dry design and good early sand ability allow you to get in and out of your jobs more quickly.

**Recommended Substrates:** Concrete/Masonry, Gypsum Wallboard-Drywall, Plaster & Wood.

**Application:** Stir thoroughly. When using more than one can of the same color, intermix to ensure color uniformity. Apply with a high quality brush, roller or by spray equipment. For airless spray application, use tip size .015"-.021" and pressure range of 1500-2000 psi. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. Brush: polyester/nylon brush. Roller: 3/8"-1/2" nap roller cover. Do not thin. Permissible temperatures during application: Material: 50 to 90°F Ambient: 50 to 90°F Substrate 50 to 90°F.

**Product Type:** Vinyl Acrylic Latex  
**Volume Solids:** 29% ± 2%  
**Weight Solids:** 46% ± 2%  
**Sheen:** Flat  
**VOC:** <100 g/L (0.8 lbs./gal.)  
**Dry Film Thickness:** 1.2-1.5 mils  
**Wet Film Thickness:** 4.0-5.3 mils  
**Flash Point:** Over 200°F (93°C)

**Dry Time at 77°F at 50% relative humidity:** to touch = 30 minutes; recoat = 2 hours. Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

**Coverage:** Approximately 300-400 sq. ft. (28-37 sq. meters) per U.S. Gallon (3.78L) on primed, smooth, nonporous surfaces.

**Clean Up:** Clean tools with warm, soapy water.

**Disposal:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**General Surface Preparation:** Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough and patched surfaces. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**Precautions:** **WARNING! HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT AND EYE IRRITATION. DO NOT SWALLOW.** Avoid contact with eyes. Avoid breathing vapor or mist. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note:** These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555.