



**SPEC-PRO®
3000
Series**

SPEC-PRO 3000 Interior Semi-Gloss Latex (3501)

SPEC-PRO 3000 Interior Semi-Gloss Latex (3501): Professional grade paint for commercial and residential use that exhibits good washing characteristics. May be applied on walls and trim in kitchens, hallways, bathrooms, or other areas where routine maintenance is required. This product dries quickly, resists spattering and has low odor during application.

Recommended Substrates: Drywall, plaster, wood, metal and masonry.

Application: Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and SDS information prior to use. Refer to Safety Data Sheet for additional health and safety information. Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. Roller: 9.5 mm to 31.8 mm (3/8" to 1 1/4") nap, depending on surface texture. Tip size and atomization pressure will vary with type of equipment, viscosity and temperature. A tip size of .017-0.21 will provide the most satisfactory spray pattern. If necessary product may be thinned up to 15% with clean water for spray application. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. Brush used should be polyester or nylon filament. Apply only when air and surface temperatures are 50°F and when the air and surface temperatures will remain above 50°F for the next 24 hours.

Product Type: Vinyl Acrylic

Volume Solids: 31.0 ± 1.0%

Weight per 3.79L: 4.6kg (10.2lbs.)

Sheen: Semi-Gloss

VOC: 98 g/L (0.37kg (0.82lbs.)/3.79L)

Dry Film Thickness: 1.3 to 1.7 mils

Wet Film Thickness: 4 to 5.3 mils

Dry Time at 77°F at 50% relative humidity: to touch = 30 minutes; recoat = 4 hours; to full cure = 10 days; drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

Coverage: Approximately 300-400 sq. ft./gal. (27.9-37.2 sq. m/3.79L) per U.S. Gallon (3.79L) on smooth, nonporous surfaces.

Clean Up: Warm, soapy water.

Flash Point: N/A

General Surface Preparation: Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, peeling or flaking paint, water soluble materials and mildew. Remove any peeling or flaking paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections. New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. **Environmental Health & Safety Information:** Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

Warning: If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php