



SPEC-PRO Buildermax Interior Low Sheen Eggshell (34201 and 34202)

SPEC-PRO Buildermax Interior Low Sheen Eggshell is a self-priming latex that features exceptional hide and coverage. It provides uniform finish, is stain resistant and is ideal for use on properly prepared and primed interior walls and ceilings.

Recommended Substrates: Concrete/Masonry Block, Gypsum Wallboard-Drywall, Plaster and Wood.

Application: Stir thoroughly before and occasionally during use. When using more than one can of the same color, intermix to ensure color uniformity. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. **USE ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available by calling (412) 492-5555. Apply with a high quality brush, roller, paint pad, or by spray equipment. For airless spray: pressure 1500-2000 psi, tip 0.015" - 0.019". Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. Brush: Polyester/Nylon Brush. Roller: 3/16" - 3/8" nap roller cover. Thinning: No thinning is usually required. If necessary add up to 1/4 pint (118 mL) of water per gallon (3.78 L) of paint. Permissible temperatures during application are between 50 to 90°F.

Product Type: Vinyl Acrylic Latex
Volume Solids: 32% +/- 2%
Weight Solids: 46% +/- 2%
Weight Per Gallon: 10.5 lbs. ± 0.2 lbs.
Flash Point: 200°F. or greater
Sheen: Eggshell: 4 to 8 (60° Gloss Meter)
Wet Film Thickness: 4.0 mils
Dry Film Thickness: 1.3 mils
VOC: <50 g/L (0.4 lbs./g)

Dry Time: to touch = 1 hour; recoat = 4 hours; Dry time @ 77 degrees Fahrenheit at 50% relative humidity. Full Cure: 30 days.

Dry times listed may vary depending on temperature, humidity, film build, color and air movement.

Clean Up: Wipe up spills immediately with a damp cloth or sponge. Wash brushes, rollers and other painting tools with soap and water immediately after use. Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

Disposal: Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

General Surface Preparation: Surfaces to be coated must be dry, clean, sound and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines and dust. Remove loose paint, chalk and all glossy, rough and patched surfaces. Feather back all rough edges to sound surface by sanding. Masonry and plaster surfaces must be allowed to cure for 30 days prior to painting. Uncoated substrates, repaired surfaces or lightly stained areas may require more than one coat.

Limitations of Use: FOR INTERIOR USE ONLY. For severe stains, water marks and challenging conditions use the appropriate high-quality primer. Not recommended for steps or floors.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.