



SPEC-PRO Buildermax TRIM-PRO Interior Semi-Gloss Latex (34501)

SPEC-PRO Buildermax TRIM-PRO is an interior semi-gloss latex formulated to meet the performance requirements of professional applicators. TRIM-PRO provides a smooth, high-lustre finish to interior walls, ceilings and trim in any room. It is also recommended for use on countertops, shelves and for dirt-and grease-prone areas requiring frequent washings with mild, non-abrasive household cleaners. It dries fast and has good block resistance.

Recommended Substrates: Properly prepared Wallboard, Wallpaper (w/o metallic design), Cured Plaster and Masonry, Wood and Metal Surfaces.

Application: Stir thoroughly. When using more than one can of the same color, intermix to ensure color uniformity. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. **USE ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available by calling 1 (866) 437-5863. Apply with a high quality brush, roller, paint pad, or by spray equipment. For airless spray: pressure 2000 psi, tip 0.017" - 0.021". Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. Brush: Polyester/Nylon Brush. Roller: 3/16" - 3/8" nap roller cover. Thinning: No thinning is usually required. If necessary add up to 1/4 pint (118 mL) of water per gallon (3.78 L) of paint. Permissible temperature during application is between 50 to 90°F.

Product Type: 100% Acrylic Latex
Volume Solids: 30.0 ± 2.0%
Weight Solids: 41 ± 2.0%
Weight Per Gallon: 10 lbs. ± 0.2 lbs.
Flash Point: 200°F. or greater
Sheen: Semi-gloss (40-60 (60° Gloss Meter))
Wet Film Thickness: 4.0 mils minimum to 4.6 mils maximum
Dry Film Thickness: 1.2 mils minimum to 1.4 mils maximum
VOC: 0.89 lbs/gal (106.80 g/L)

Dry Time: to touch = 1 hour; recoat = 4 hours; Dry time @ 77 degrees Fahrenheit at 50% relative humidity.
Full Cure: 30 days.

Dry times listed may vary depending on temperature, humidity, film build, color and air movement.

Clean Up: Warm, soapy water.

Disposal: Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

General Surface Preparation: Surfaces to be coated must be dry, clean, smooth, and free from all contaminants. All cracks and other surface imperfections must be repaired and spot primed. Dull glossy surfaces by sanding. Prime all bare wood, plaster, masonry, metal, patched and porous surfaces with the appropriate primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.