



SPEC-PRO 2000 Interior Primer (SP2000)

SPEC-PRO 2000 Interior Primer: A contractor-grade interior primer for use on new drywall. Seals drywall and prepares for topcoating. Recommended for use under flat and low-sheen topcoats.

Recommended Substrates: New Drywall.

Application: Mix thoroughly before use. May be applied by brush, roller or spray. No thinning required. For airless spray, use a .015" tip. Adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

Product Type: Vinyl Acrylic Resin
Volume Solids: 15 ± 1.0%
Gloss: 3 to 9 units at 85°
VOC: max of 50 g/L (.42 lbs/gal)

Dry Time 77°F (25°C) & 50% RH: to touch = 30 minutes; recoat = 2 hours

Coverage: 250-300 sq ft/gallon. Actual coverage may vary depending on substrate and application method.

Clean Up: Warm, soapy water.

Disposal: Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Do not pour down a drain or storm sewer.

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances. Joint compound must dry for two days before priming. Remove sanding dust. Prime with this product. Previously painted surfaces should be washed to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare drywall with this product.

Warning: Causes eye, skin and respiratory tract irritation. May be harmful if swallowed. Use only with adequate ventilation. Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Contains Ethylene Glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.

In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed, get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Obtain and read the MSDS prior to using this product. **KEEP OUT OF REACH OF CHILDREN.**