



SPEC-PRO® 4000 ZERO VOC INTERIOR WALL & CEILING LATEX SEMI-GLOSS (Z4501-Z4503)

SPEC-PRO® 4000 ZERO VOC SEMI-GLOSS: A durable, quality interior vinyl acrylic paint designed for new and repaint applications where speed of application is most important in both the commercial and multi-family markets. This zero-VOC**, low odor paint enables a space to be painted while occupied while delivering the durable product performance required. Good adhesion and application properties on walls, ceilings and trim surfaces. Recommended on interior walls, ceilings and trim where a semi-gloss finish is desirable.

Recommended Substrates: Concrete, Concrete/Masonry Block, Ferrous Metal, Gypsum Wallboard-Drywall, Plaster and Wood.

Application: Stir thoroughly before using and occasionally when in use. When using more than one container of the same color, intermix to ensure color uniformity. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and SDS information prior to use. Apply with a high quality brush, roller, paint pad, or by airless spray equipment. Brush used should be Polyester/Nylon. Use a 3/16"-3/8" nap roller cover, depending on surface texture. Apply coating evenly while maintaining a wet edge to prevent lapping. Thinning is not usually required. If necessary, add no more than 1/4 pint (118 mL) of water per gallon (3.78L) of paint. Airless Spray: Pressure 2000 psi, tip 0.015" - 0.021". Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. Permissible temperatures during application, including: Material, Ambient and Substrate 50 to 90°F.

Product Type: Vinyl Acrylic Latex

Volume Solids: 30% ± -2%

Weight Solids: 40% ± -2%

Sheen: Semi-Gloss

VOC: 0 g/L (0 lb/gal)

Dry Film Thickness: 1.2 mils

Wet Film Thickness: 4.0 mils

Dry Time at 77°F at 50% relative humidity: to touch = 1 hour; recoat = 4 hours; to recoat = 30 days. Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

Coverage: Approximately 400sq. ft./gal. per U.S. Gallon (3.78L) on smooth, nonporous surfaces.

Clean Up: Clean tools, equipment, and work area with warm soapy water.

Disposal: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

General Surface Preparation: Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, efflorescence, rust, and chalk. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding. Prime all bare and porous substrates with an appropriate primer. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Warning: HARMFUL IF SWALLOWED. Sanding and grinding dusts may be harmful if inhaled. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warning encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. **KEEP OUT OF REACH OF CHILDREN.**

Spectrum Paint Company, 15247 E Skelly Dr., Tulsa, OK 74116

For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).